

EST Group, a business unit of Curtiss-Wright Flow Control Company

2701 Township Line Road, Hatfield, PA 19440

Telephone: (215) 721-1100 800-355-7044 Fax: (215) 721-1101

E-Mail: est-info@curtisswright.com Website: estgroup.cwfc.com

GripTight® High Pressure Test Plug

I.D. sealing test plug for high pressure hydrostatic testing of pipe, pipelines and pressure vessels.

Note: Never use a test pressure greater than the weakest component in the system can handle. Test Pressure specified in table is equivalent to 80% of the pressure that will yield ASTM A106 Grade B pipe. The test pressure for higher and lower strength pipes will differ proportionally. The maximum test pressure for higher strength pipe must never exceed the highest test pressure listed for that pipe O.D.

Specifications subject to change without notice.



Results 101 - 125 of 153

Item #	Nominal Pipe Size (in)	Nominal Pipe Schedule	Pipe I.D. Size Range (in)	Pipe I.D. Size Range (mm)	Plug O.D. (in)	Plug O.D. (mm)	Maximum Test Pressure (psi)	List Price
GT-14P120	14	120	11.78 to 12.18	299.212 to 309.372	11.63	295.402	4713	QUOTE
GT-12P40	12	40	11.91 to 12.19	302.514 to 309.626	11.82	300.228	1840	QUOTE
GT-12P30	12	30	12.06 to 12.27	306.324 to 311.658	11.91	302.514	1487	QUOTE
GT-14P100	14	100	12.09 to 12.45	307.086 to 316.23	11.94	303.276	4001	QUOTE
GT-12P20	12	20	12.22 to 12.41	310.388 to 315.214	12.07	306.578	1120	QUOTE
GT-12P10	12	5s	12.36 to 12.57	313.944 to 319.278	12.21	310.134	802	QUOTE
GT-14P80	14	80	12.47 to 12.78	316.738 to 324.612	12.32	312.928	3160	QUOTE
GT-14P60	14	60	12.78 to 13.05	324.612 to 331.47	12.63	320.802	2476	QUOTE
GT-14Pxs	14	xs	12.97 to 13.22	329.438 to 335.788	12.82	325.628	2071	QUOTE
GT-14P40	14	40	13.09 to 13.33	332.486 to 338.582	12.94	328.676	1807	QUOTE
GT-14PSTD	14	30	13.22 to 13.44	335.788 to 341.376	13.07	331.978	1540	QUOTE
GT-14P20	14	20	13.34 to 13.55	338.836 to 344.17	13.2	335.28	1276	QUOTE
GT-14P10	14	5s	13.47 to 13.82	342.138 to 351.028	13.44	341.376	1018	QUOTE
GT-16P120	16	120	13.53 to 13.96	343.662 to 354.584	13.38	339.852	4587	QUOTE
GT-16P100	16	100	13.91 to 14.29	353.314 to 362.966	13.76	349.504	3839	QUOTE
GT-16P80	16	80	14.28 to 14.62	362.712 to 371.348	14.13	358.902	3109	QUOTE
GT-16P60	16	60	14.66 to 14.95	372.364 to 379.73	14.51	368.554	2390	QUOTE
GT-16P40	16	40	14.97 to 15.22	380.238 to 386.588	14.82	376.428	1805	QUOTE
GT-16PSTD	16	30	15.22 to 15.44	386.588 to 392.176	15.07	382.778	1343	QUOTE
GT-18P120	18	120	15.22 to 15.69	386.588 to 398.526	15.07	382.778	4,600	QUOTE
GT-16P20	16	20	15.34 to 15.55	389.636 to 394.97	15.2	386.08	1113	QUOTE
GT-16P10	16	5s	15.47 to 15.81	392.938 to 401.574	15.32	389.128	889	QUOTE

GT-18P100	18	100	15.66 to 16.07	397.764 to 408.178	15.51	393.954	3,825	QUOTE
GT-18P80	18	80	16.09 to 16.45	408.686 to 417.83	15.94	404.876	3,069	QUOTE
GT-18P60	18	60	16.47 to 16.78	418.338 to 426.212	16.32	414.528	2,430	QUOTE

Results 101 - 125 of 153