

EST Group, a business unit of Curtiss-Wright Flow Control Company

2701 Township Line Road, Hatfield, PA 19440

Telephone: (215) 721-1100 800-355-7044 Fax: (215) 721-1101

E-Mail: est-info@curtisswright.com Website: estgroup.cwfc.com



GripTight® High Pressure Test Plug

I.D. sealing test plug for high pressure hydrostatic testing of pipe, pipelines and pressure vessels.

Note: Never use a test pressure greater than the weakest component in the system can handle. Test Pressure specified in table is equivalent to 80% of the pressure that will yield ASTM A106 Grade B pipe. The test pressure for higher and lower strength pipes will differ proportionally. The maximum test pressure for higher strength pipe must never exceed the highest test pressure listed for that pipe O.D.

Specifications subject to change without notice.

Results 151 - 153 of 153

Item #	Nominal Pipe Size (in)	Nominal Pipe Schedule	Pipe I.D. Size Range (in)	Pipe I.D. Size Range (mm)	Plug O.D. (in)	Plug O.D. (mm)	Maximum Test Pressure (psi)	List Price
GT-24PXS	24	xs	22.97 to 23.25	583.438 to 590.55	22.75	577.85	1,191	QUOTE
GT-24PSTD	24	20	23.22 to 23.47	589.788 to 596.138	23	584.2	889	QUOTE
GT-24P10	24	5s	23.47 to 23.74	596.138 to 602.996	23.25	590.55	589	QUOTE

Results 151 - 153 of 153